

# 3EG-EA Flex-Shaft Grinder



- 1 1/2 H.P., 115/230 volt, 3450 RPM, 60 Hz., single phase, AC electric motor (P.N. FS102)
- Three Caster swiveling tripod motor mount with carrying handle (P.N. 3927)
- 7 ft. Flexible housing (P.N. 57143A)
- Wet angle head, 4 spline, 1:1 ratio (P.N. 56934)
- Optional mountings available: Pedestal Mount, Hanger Bail Mount, Low Caster Base (tripod), Round Base

## FOR 1 1/2 HP 4 SPLINE MACHINES (3EG-EA)

Spindles - Fits 4 spline drive shafts. Spindle arbors have standard 5/8" - 11 threaded shaft to accommodate 5/8" threaded insert cup type and 5/8" bushed hole edge type grinding wheels or 3/4" pilot thread to accommodate 3/4" bushed hole cup and edge type grinding wheels.

3/4" Thread	5/8" Thread	Spindle Description
3430W	56885	Cove Base, Wet, 1:1, 3450 RPM
3430D	56890	Cove Base, Dry, 1:1, 3450 RPM
23500-S	56902	Straight, Dry, 1:1, 3450 RPM
30811B	56930	Angle, Dry, 1:1, 3450 RPM
	56930A	Angle, Dry, 2:1, 1725 RPM
	56930B	Angle, Dry, 4:1, 865 RPM
3115B	56934	Angle, Wet, 1:1, 3450 RPM
	56934A	Angle, Wet, 2:1, 1725 RPM
	56923B	Angle, Wet, 4:1, 865 RPM
22610B	56959E	Angle, Dry, 10:1, 345 RPM



222 1st Avenue NW • Watertown, SD 57201  
 Phone: (605) 882-3888 • Fax: (605) 882-0778  
 Email: [info@terrco.com](mailto:info@terrco.com) • Website: [www.terrco.com](http://www.terrco.com)

