

3EG-EA Flex-Shaft Grinder



- 1 1/2 H.P., 115/230 volt, 3450 RPM, 60 Hz., single phase, AC electric motor (P.N. FS102)
- Three Caster swiveling tripod motor mount with carrying handle (P.N. 3927)
- 7 ft. Flexible housing (P.N. 57143A)
- Wet angle head, 4 spline, 1:1 ratio (P.N. 56934)
- Optional mountings available: Pedestal Mount, Hanger Bail Mount, Low Caster Base (tripod), Round Base

FOR 1 1/2 HP 4 SPLINE MACHINES (3EG-EA)

Spindles - Fits 4 spline drive shafts. Spindle arbors have standard 5/8" - 11 threaded shaft to accommodate 5/8" threaded insert cup type and 5/8" bushed hole edge type grinding wheels or 3/4" pilot thread to accommodate 3/4" bushed hole cup and edge type grinding wheels.

| 3/4" Thread | 5/8" Thread | Spindle Description |
|-------------|-------------|-------------------------------|
| 3430W | 56885 | Cove Base, Wet, 1:1, 3450 RPM |
| 3430D | 56890 | Cove Base, Dry, 1:1, 3450 RPM |
| 23500-S | 56902 | Straight, Dry, 1:1, 3450 RPM |
| 30811B | 56930 | Angle, Dry, 1:1, 3450 RPM |
| | 56930A | Angle, Dry, 2:1, 1725 RPM |
| | 56930B | Angle, Dry, 4:1, 865 RPM |
| 3115B | 56934 | Angle, Wet, 1:1, 3450 RPM |
| | 56934A | Angle, Wet, 2:1, 1725 RPM |
| | 56923B | Angle, Wet, 4:1, 865 RPM |
| 22610B | 56959E | Angle, Dry, 10:1, 345 RPM |



222 1st Avenue NW • Watertown, SD 57201
 Phone: (605) 882-3888 • Fax: (605) 882-0778
 Email: info@terrco.com • Website: www.terrco.com

