

# 5FG-EA Flex-Shaft Grinder



- 2 H.P., 220 or 440 Volt, 3450 RPM, 60 Hz., Three Phase, AC electric motor (P.N. FS117)
- Three Caster swiveling tripod motor mount with carrying handle (P.N. 3927)
- 7 ft. Flexible Shaft, 6 spline ( P.N. 32957A)
- 7 ft. Flexible Housing (P.N. 4790A)
- Wet angle head, 6 spline, 1:1 ratio, (P.N. 56961 or 31171C)
- Optional mounts available: Pedestal Mount, Hanger Bail Mount, Low Caster Base (tripod), Round Base

## FOR 2 HP 6 SPLINE MACHINES (5FG & 6EG)

Spindles - Fits 6 spline drive shafts. Spindle arbors have standard 5/8" - 11 threaded shaft to accommodate 5/8" threaded insert cup type and 5/8" bushed hole edge type grinding wheels or 3/4" pilot thread to accommodate 3/4" bushed hole cup and edge type grinding wheels.

3/4" Thread	5/8" Thread	Description
23500	56897	Straight, Dry, 1:1, 3450 RPM
31161C	56950	Angle, Dry, 1:1, 3450 RPM
	56950A	Angle, Dry, 2:1, 1725 RPM
	56950B	Angle, Dry, 4:1, 865 RPM
31171C	56961	Angle, Wet, 1:1, 3450 RPM
	56961A	Angle, Wet, 2:1, 1725 RPM
	56961B	Angle, Wet, 4:1, 865 RPM
	57076	Cove Base, Dry, 1:1, 3450 RPM
	57077	Cove Base, Wet, 1:1, 3450 RPM



222 1st Avenue NW • Watertown, SD 57201  
 Phone: (605) 882-3888 • Fax: (605) 882-0778  
 Email: [info@terrco.com](mailto:info@terrco.com) • Website: [www.terrco.com](http://www.terrco.com)

