

Model 7500



HP/KW	10/7.5
SWEEP OF DISCS	20" (508 mm)
ABRASIVE PRESSURE	545 lbs (247 kg)
WIDTH OF MACHINE	21" (533 mm)
LENGTH OF MACHINE	48-3/4" (1238 mm)
HEIGHT OF MACHINE	47" (1194 mm)
NET WEIGHT	795 lbs (360 kg)
SHIPPING WEIGHT	865 lbs (392 kg)
WATER TANK	15 gallon (56,8 L)
POWER CORD (6-3)	100 ft (30,5 m)

ELECTRICAL OPTIONS

VOLTAGE	230	230	230	460
PHASE	1	3	1	3
DRIVE	MANUAL	MANUAL	VARIABLE	VARIABLE
AMP DRAW	40	20	20	12
BREAKER (AMPS)	60	30	30	30
STONE HOLDER RPM	821	821	420-650	420-650

- Mild Steel Guards or Water Tank
- Removable weights for easy transportation
- Four 42 lbs. Pocket Weights
- Direct Drive, No Belts
- Setup for new speed shift diamond disc system, preventing throwing stones

PRODUCTION RATES

- Mastic removal rate of 500 sq. ft. per hour
- Thin-Set removal rates of 800 sq. ft. per hour
- Thin-Mil coatings removal of 600 sq. ft. per hour



222 1st Avenue NW • Watertown, SD 57201
 Phone: (605) 882-3888 • Fax: (605) 882-0778
 Email: info@terrco.com • Website: www.terrco.com

