

5FG-EA Flex-Shaft



- 2 HP, 220V or 440V, 3,450 RPM, 60 Hz, three phase, AC electric motor (P.N. FS117)
- Three caster swiveling tripod motor mount with carrying handle (P.N. 3927)
- 7' flexible shaft, 6 spline (P.N. 32957A)
- 7' flexible housing (P.N. 4790A)
- Wet angle head, 6 spline, 1:1 ratio (P.N. 56961 or 31171C)
- Multiple mounting options available

- Fits 6 spline drive shafts.
- Spindle arbors have standard 5/8"-11 thread shaft to accommodate 5/8" thread insert cup type and 5/8" bushed hole edge type grinding wheels.
- Or 3/4" pilot thread to accommodate 3/4" bushed hole cup and edge type grinding wheels.

3/4" Thread	5/8" Thread	Spindle Description
23500	56897	Straight, Dry, 1:1, 3,450 RPM
31161C	56950	Angle, Dry, 1:1, 3,450 RPM
	56950A	Angle, Dry, 2:1, 1,725 RPM
	56950B	Angle, Dry, 4:1, 865 RPM
31171C	56961	Angle, Wet, 1:1, 3,450 RPM
	56961A	Angle, Wet, 2:1, 1,725 RPM
	56961B	Angle, Wet, 4:1, 825 RPM
	57076	Cove Base, Dry, 1:1, 3,450 RPM
	57077	Cove Base, Wet, 1:1, 3,450 RPM

Optional shafts (6 spline) and housings for 5FG-EA, 6EG-EA, 5FG & 6EG Base Machines

Part #	Description
32956	7/16" diameter X 6' long flexible shaft
32956D	7/16" diameter X 7' long flexible shaft
32957	5/8" diameter X 6' long flexible shaft
32957A	5/8" diameter X 7' long flexible shaft
32957B	5/8" diameter X 10' long flexible shaft
4790	5/8" I.D. X 6' flexible housing
4790A	5/8" I.D. X 6' flexible housing
4790B	5/8" I.D. X 6' flexible housing
4860	1/2" I.D. X 6' flexible housing
4860A	1/2" I.D. X 6' flexible housing

95+ YEARS



Terrco® Inc.

222 1st Avenue NW • Watertown, SD 57201

Phone: (605) 882-3888 • Fax: (605) 882-0778

Website: www.terrco.com • Email: info@terrco.com

